



PH3000
Sensor



Description

The Greenspan pH3000 is a complete self contained pH measurement and data logging system for monitoring of pH in a wide variety of environmental applications.

The sensor utilises a robust gel filled pH electrode together with optical isolation and advanced signal conditioning to ensure long term accurate data. The sensor also features a field replaceable electrode to further improve long term performance and reduce field visits.

The internal data logger provides long term data collection at remote sites, and options for remote telemetry connection. The Sensor can be fitted with an external cable, or with an on board battery pack for true stand alone operation. Other cable options can provide serial output in SDI12 format for connection to external Data Loggers or process controller.

The sensor is ideal for use in environmental water monitoring applications, including tidal and estuary monitoring. A durable acetal body with double O ring design ensures suitability for the harshest environment applications.

The pH3000 sensor is easy to configure and provides a reliable solution for long term monitoring. For more information please contact your nearest sales office.

Features

- Field replaceable gel filled pH electrode
- Optically isolated signal conditioning electronics
- Internal temperature compensation
- Low power energy requirements
- Optional battery pack for true stand alone operation
- Telemetry communication options
- SDI12 cable adaptor unit for connection into data logger or controller.

Benefits

- High reliability and minimal field servicing means lower costs
- Operation for up to 12 months at a remote site
- Internal Data Logger means no wiring, easy configuration and lower cost
- Easy data collection using a PC with Windows software.

Applications

- Monitoring of streams and rivers, lakes and urban waterways
- Water quality studies and catchment management
- Water supply storage including stratification studies
- Water and wastewater treatment monitoring
- Groundwater analysis and monitoring
- Tidal, estuary and oceanographic monitoring.

Dimensions



PH3000 Specification

Measurement Technique	Gel-filled glass electrode with internal Ag/AgCl reference Field replaceable electrode
Sensor Range (factory calibrated)	2-12 pH
Sensor Outputs	Internal data logger – serial output via software Optional adaptor provides SDI12 serial output (3 wire)
Resolution	0.001 pH, 0.05°C temperature
Accuracy	+/-0.2pH, +/- 0.2°C temperature, +/- 0.5V battery
Cable Type	Polyurethane sheathed cable, OD 8mm, with 3mm vent tube, moulded entry, HS7 connector
Cable Lengths	10, 20, 30, 50, 100, 150m (32, 65, 100, 165, 325, 490 ft)
Power supply	8 to 30vdc external supply or on board battery pack (option)
Reverse Polarity Protection	Yes
Surge Current Protected	To 2kV
Warm up time to stable reading	2 sec
Current Consumption	Sleep 0.5mA, Logging 21mA, Communicating 30mA
On Board Battery Pack (option)	Housing screws to sensor size (OD x L) 47mm x 250mm
Battery Capacity	9 x Lithium AA (3.6Volt) – Total capacity 5.2Ah @ 10.8v
Typical Field Life (Batt Pack)	Over 6 months remote operation @ 30 min logging
Internal data logger	Non-volatile, battery backed ram with real time clock
Memory size	2Mb capacity, with user selectable wrap function
Measuring units	User definable
Data Storage	100 000 readings (typically 5 minute data for >12 months)
Logging frequency	User selectable from 1 second up to once per day
Averaging Alarms	User selectable via supplied Smartcom software
Operating temperature	0-50°C
Storage Temperature	-5°C - +60°C
Depth Rating (water column)	100m
Weight	500g plus cable weight (665g per 10m length)
Dimensions (L x OD)	384.20mm x 47mm (15.13" x 1.85") or 584.20mm x 47mm (23.0" x 1.85") with battery housing
Wetted Materials	UPVC, Acetal, 316 Passivated Stainless Steel, Polyurethane, Viton



Optional Extras and Accessories

- Moulded Cable (specify required length above)
- On-board battery pack (includes housing and battery pack)
- SDI12 Adaptor (connects to end of sensor cable for serial output to logger).

How to Order

The following information will be required:

- Model PH3000
- Please specify cable or battery pack and any other options.



Australia

Head Office
Goyen Controls Co Pty Ltd
268 Milperra Road
Milperra, NSW 2214

Telephone: 1800 805 372
Facsimile: 1300 658 799

Sales and Service
Queensland, South Australia
Victoria, Western Australia

Telephone: 1800 805 372
Facsimile: 1300 658 799

USA

Goyen Valve Corporation
1195 Airport Road
Lakewood
New Jersey 08701, USA

Telephone: 1 732 364 7800
Facsimile: 1 732 364 1356

Asia

Goyen Controls Co Pty Ltd
Shanghai Representative Office
1209 Greenland Business Centre
1258 Yu Yuan Road
Shanghai PC200050, CHINA

Telephone: 86 21 5239 8810
Facsimile: 86 21 5239 8812

Goyen Controls Co Pty Ltd
73-M Jalan Mega Mendung
Kompleks Bandar OUG
58200 Kuala Lumpur, MALAYSIA

Telephone: 60 37 987 6839
Facsimile: 60 37 987 7839

Greenspan Singapore Pte Ltd
02-01, Minwa Industrial Building
39 Genting Lane
Singapore 349554

Telephone: 65 6748 0140
Facsimile: 65 6748 2534

Europe

Goyen Controls Co UK Ltd
Unit 3B Beechwood
Chineham Business Park
Basingstoke, Hampshire, RG24 8WA
UNITED KINGDOM

Telephone: 44 1256 817 800
Facsimile: 44 1256 843 164

Tyco Umwelttechnik GmbH
Im Petersfeld 6
D-65624 Altendiez
GERMANY

Telephone: 49 6432 1001/1002
Facsimile: 49 6432 63810

Mecair S.r.l.
Via per Cinisello 97
20054 Nova Milanese
Milano,
ITALY

Telephone: 39 362 375 118
Facsimile: 39 362 375 124